



2.6W



Coastal protected



IP65 ideal for outdoor environments

WL060

Straight to mains LED halo / flood wall light

Features

IP rating	IP65
CSP Switchable	Single CCT
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	0.6kg
Inrush Current	9A 0.8ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
SELV	SELV
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Bi-directional wall light offering decorative halo effect and functional downward flood light
- Complete with wall fixings and waterproof crimp connectors
- Mains voltage wall light

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL060 NW	Silver	2.6W	4000K	120°	82	32	46	
WL060 WW	Silver	2.6W	3000K	120°	58	22	26	
WL060 27	Silver	2.6W	2700K	120°	56	22	25	

Wiring Information

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

Accessories

N/A	No accessories required
-----	-------------------------

