



collingwood



2.6W



Coastal protected



IP65 ideal for outdoor environments

### Features

|                        |             |
|------------------------|-------------|
| IP rating              | IP65        |
| CSP Switchable         | Single CCT  |
| Tilttable              | No          |
| Dimmable Option        | No          |
| LED Lifetime           | L70 70,000h |
| Colour Rendering Index | CRI>80      |
| Colour Consistency     | SDCM3       |

### Installation Information

|                             |                    |
|-----------------------------|--------------------|
| Input                       | 220-240V AC        |
| Maximum Ambient Temperature | 40°C               |
| Weight                      | 0.6kg              |
| Inrush Current              | 9A 0.8ms           |
| Construction Material       | Anodised aluminium |
| UK Bathroom Zone            | 2                  |
| SELV                        | Yes                |
| Electric Class (1, 2, 3)    | 1                  |
| Earth Leakage               | 0.1mA              |
| Suitable for coastal areas  | Yes                |

### Guarantee

Warranty 7 years

### Features & benefits

- Bi-directional wall light offering decorative halo effect and functional downward flood light
- Complete with wall fixings and waterproof crimp connectors
- Mains voltage wall light

### Patent Information

GB2487912 GB2512715

### Wiring Information

|                         |          |
|-------------------------|----------|
| Cable / Flying Lead     | 0.3m     |
| Type of Wiring Required | Parallel |

### LED Driver

| Driver                       | Input    | SELV | Dimming | Bathroom Zone | Min | Max |
|------------------------------|----------|------|---------|---------------|-----|-----|
| N/A (integrated SELV driver) | 220-240V | Yes  | No      | 2             | N/A | N/A |

### Accessories

|                               |
|-------------------------------|
| N/A (No Accessories required) |
|-------------------------------|

