

5.1W

Coastal protected

IP65 ideal for outdoor environments

## FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution.

Ideal for framing entrances and illuminating columns with its bi-directional lights

Anodised Aluminium is sleek and durable

Long lifetime of 70,000hrs

Mains voltage wall light



## WL070

Straight to mains, high output LED wall light

### FEATURES

<b>IP rating</b>	IP65
<b>CSP Switchable</b>	Single CCT
<b>Dimmable Option</b>	No
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	40°C
<b>Weight</b>	0.9kg
<b>Inrush Current</b>	60A 0.037ms
<b>Construction Material</b>	Anodised aluminium
<b>UK Bathroom Zone</b>	2
<b>Electric Class (1, 2, 3)</b>	I
<b>Suitable for coastal areas</b>	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @1m	Energy
WL070SNBM27	Silver	5.1W	2700K	12°	510-255	100	3147-1573	
WL070SNBM30	Silver	5.1W	3000K	12°	550-275	108	3394-1697	
WL070SNBM40	Silver	5.1W	4000K	12°	560-280	110	3455-1727	
WL070BNBM27	Black	5.1W	2700K	12°	510-255	100	3147-1573	
WL070BNBM30	Black	5.1W	3000K	12°	550-275	108	3394-1697	
WL070BNBM40	Black	5.1W	4000K	12°	560-280	110	3455-1727	
WL070CNBM27	Copper	5.1W	2700K	12°	510-255	100	3147-1573	
WL070ZNBM27	Bronze	5.1W	2700K	12°	510-255	100	3147-1573	
WL070ZNBM30	Bronze	5.1W	3000K	12°	550-275	108	3394-1697	
WL070CNBM30	Copper	5.1W	3000K	12°	550-275	108	3394-1697	

12°

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	0.3m
<b>Type of Wiring Required</b>	Parallel

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A

### ACCESSORIES

No accessories required
-------------------------