



# WL070RGBW

Up / down LED colour change wall light (24W max.)

## FEATURES

IP rating	IP65
CSP Switchable	RGBW
Tilttable (°)	Fixed
Dimmable Option	No
LED Lifetime	L50 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

## INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	0.9kg
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes

## RGBW Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
WL070RGBW	6W	White (4000K)	45°	200	67	154
WL070RGBW	4.0W	Red	45°	145	73	60
WL070RGBW	6.0W	Green	45°	230	77	168
WL070RGBW	6.0W	Blue	45°	38	13	1

Energy rating is a reflection of the LED light source.

## WIRING INFORMATION

Cable / Flying Lead	1x 5-core ribbon cable
Type of Wiring Required	Series
Input Cable Type	5-core ribbon cable

## LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	1
CCDRV75DMX	220-240V	Yes	Yes	2	1
CCDRV75RF	220-240V	Yes	Yes	2	1

## ACCESSORIES

JB7	5 pole screw terminal IP68 connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
LEDRGBWEXT	Colour change Plug & Play 1m extension lead	Sold Separately
CCRFCNVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately



RGBW



Coastal protected



IP65 ideal for outdoor environments

## WARRANTY

Warranty 5 years

## FEATURES & BENEFITS

Complete with wall fixings for easy installation

Projects light in two directions

Separate white LED for permanent use

Anodised aluminium for use in outdoor and indoor environments

Compatible with a large range of controllers

PATENT: GB2487912 GB2512715

BEAM ANGLE: 45°

