



WL070RGBW

Up / down LED colour change wall light (24W max.)

Features

IP rating	IP65
CSP Switchable	RGBW
Tiltable	No
Dimmable Option	No
LED Lifetime	L50 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	No

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	0.9kg
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

RGBW Photometrics

Product Code	Wattage	Colour	Beam Angle	lm	lm/W	lx @ 1m
WL070RGBW	6W	White (4000K)	45°	200	67	154
WL070RGBW	4.0W	Red	45°	145	73	60
WL070RGBW	6.0W	Green	45°	230	77	168
WL070RGBW	6.0W	Blue	45°	38	13	1

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	1x 5-core ribbon cable
Type of Wiring Required	Series
Input Cable Type	5-core ribbon cable

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Max
CCDRV75DALI	220-240V	Yes	Yes (Dali)	2	1
CCDRV75DMX	220-240V	Yes	Yes	2	1
CCDRV75RF	220-240V	Yes	Yes	2	1

Accessories

JB7	5 pole screw terminal IP68 connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
LEDRGBWEXT	Colour change Plug & Play 1m extension lead	Sold Separately
CCRFCONVWIFI / CCREMOTEB / CCWALLRF(B/W)	4/8 zone RF control for RGB & RGBW system	Sold Separately



RGBW



Coastal protected



IP65 ideal for outdoor environments

Guarantee

Warranty 5 years

Features & benefits

- Complete with wall fixings for easy installation
- Projects light in two directions
- Separate white LED for permanent use
- Anodised aluminium for use in outdoor and indoor environments
- Compatible with a large range of controllers

Patent Information

GB2487912 GB2512715

Beam angle: 45°

