

5.7W

Coastal protected

IP65 ideal for outdoor environments

## FEATURES & BENEFITS

Single LED and lens combination for maximum efficiency and optimal light distribution.

Straight to mains wall light, perfect for framing entrances and illuminating columns

Anodised Aluminium is sleek and durable

Long lifetime of 70,000hrs

## WL075

Straight to mains, high output LED wall light

### FEATURES

<b>IP rating</b>	IP65
<b>CSP Switchable</b>	Single CCT
<b>Dimmable Option</b>	No
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	40°C
<b>Weight</b>	1.2kg
<b>Inrush Current</b>	60A 0.037ms
<b>Construction Material</b>	Anodised aluminium
<b>UK Bathroom Zone</b>	2
<b>Electric Class (1, 2, 3)</b>	I
<b>Suitable for coastal areas</b>	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @1m	Energy
WL075SNBM27	Silver	5.7W	2700K	110°	515	90	2763	
WL075SNBM30	Silver	5.7W	3000K	110°	520	91	2789	
WL075SNBM40	Silver	5.7W	4000K	110°	530	93	2843	
WL075BNBM27	Black	5.7W	2700K	110°	515	90	2763	
WL075BNBM30	Black	5.7W	3000K	110°	520	91	2789	
WL075BNBM40	Black	5.7W	4000K	110°	530	93	2843	
WL075ZNBM27	Bronze	5.7W	2700K	110°	515	90	2763	
WL075ZNBM30	Bronze	5.7W	3000K	110°	520	91	2789	

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	0.3m
<b>Type of Wiring Required</b>	Parallel

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A

### ACCESSORIES

No accessories required
-------------------------

12°