

WL140A F

Straight to mains LED wall light

| FEATURES | |
|------------------------|-------------|
| IP rating | IP65 |
| CSP Switchable | Single CCT |
| Tiltable | 90° |
| Dimmable Option | Yes |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Rotation Angle | 350° |

| INSTALLATION IN | IFORMATION |
|-----------------------------|--------------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 35°C |
| Weight | 0.7kg |
| Inrush Current | 15A 0.5ms |
| Construction Material | Anodised aluminium |
| UK Bathroom Zone | 2 |
| SELV | Yes |
| Electric Class (1, 2, 3) | 1 |
| Earth Leakage | 0.1mA |

PHOTOMETRICS @ 25°C

| Product code | Finish | w | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|--------|----|--------|------|-----|------|---------|-------------|
| WL140A F WW | Black | 8W | 3000K | 38° | 413 | 52 | 1168 | A G G |

Suitable for coastal areas

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

| Cable / Flying Lead | 0.3m |
|-------------------------|----------|
| Type of Wiring Required | Parallel |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone |
|------------------------------|----------|------|---------|---------------|
| N/A (integrated SELV driver) | 220-240V | Yes | Yes | 2 |

ACCESSORIES

| N/A | No accessories required | |
|-----|-------------------------|--|



LIGHTING INNOVATION



Equivalent to 50W halogen



Complete with wall fixings and waterproof crimp connectors



Adjustable angle to direct

WARRANTY

Varranty

FEATURES & BENEFITS

Cowl desian to reduce alare

Suitable for indoor and outdoor us

PATENT: **GB2487912 GB2512715**



