

FEATURES

IP rating	IP65	
CSP Switchable	Single CCT	
Tiltable	No	
Dimmable Option	No	
LED Lifetime	L70 70,000h	
Colour Rendering Index	CRI>80	
Colour Consistency	SDCM3	

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	0.6kg
Inrush Current	9A 0.8ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

WIRING INFORMATION

Cable / Flying Lead	0.3m
Type of Wiring Required	Paralle

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

ACCESSORIES

N/A (No Accessories required)



LIGHTING INNOVATION



2.6W



Coastal protected



IP65 ideal for outdoor environments

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Bi-directional wall light offering decorative halo effect and functional downward flood light

Complete with wall fixings and waterproof crimp connectors

Mains voltage wall ligh

