

## WL160

# FEATURES IP rating

 IP rating
 IP65

 CSP Switchable
 Single CCT

 Tiltable (°)
 Fixed

 Dimmable Option
 No

 LED Lifetime
 L70 70,000h

 Colour Rendering Index
 CRI>80

 Colour Consistency
 SDCM3

#### INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	40°C		
Weight	0.6kg		
Inrush Current	9A 0.8ms		
Construction Material	Anodised aluminium		
UK Bathroom Zone	2		
SELV	Yes		
Electric Class (1, 2, 3)	1		
Earth Leakage	0.1		
Suitable for coastal areas	Yes		
Mounting Options	Wall		

#### WIRING INFORMATION

 Cable / Flying Lead
 0.3m

 Type of Wiring Required
 Parallel

#### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

### ACCESSORIES

N/A (No Accessories required)



LIGHTING INNOVATION



2.6W



Coastal protected



IP65 ideal for outdoor environments

#### WARRANTY

Warranty

7 years

#### FEATURES & BENEFITS

Bi-directional wall light offering decorative halo effect and functional downward flood light

Complete with wall fixings and waterproof crimp connectors

Mains voltage wall light

