

WL160

FEATURES IP rating IP65 CSP Switchable Single CCT

 Tiltable
 No

 Dimmable Option
 No

 LED Lifetime
 L70 70,000h

 Colour Rendering Index
 CR♭80

SDCM3

INSTALLATION INFORMATION

Input	220-240V AC	
Maximum Ambient Temperature	40°C	
Weight	0.6kg	
Inrush Current	9A 0.8ms	
Construction Material	Anodised aluminium	
UK Bathroom Zone	2	
SELV	Yes	
Electric Class (1, 2, 3)	1	
Earth Leakage	0.1mA	
Suitable for coastal areas	Yes	
Mounting Options	Wall	

WIRING INFORMATION

 Cable / Flying Lead
 0.3m

 Type of Wiring Required
 Parallel

LED DRIVER

Colour Consistency

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

ACCESSORIES

N/A (No Accessories required)



LIGHTING INNOVATION



2.6W



Coastal protected



IP65 ideal for outdoor environments

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Bi-directional wall light offering decorative half effect and functional downward flood light

Complete with wall fixings and waterproof crimp connectors

Mains voltage wall light

