



Bi-directional, straight to mains wall light



Equivalent to 35W halogen

Copper option gradually ages to offer an antique effect

WL170A

Straight to mains, up / down LED wall light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable (°)	Fixed
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	1.04kg
Inrush Current	5A 0.5ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	I
Earth Leakage	0.1

PHOTOMETRICS @ 25°C

Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m
Black	8W	4000K	18°	472-236	59	1000

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

ACCESSORIES

N/A	No accessories required
-----	-------------------------

BEAM ANGLE: 18°

