



WL170A



collingwood



Bi-directional, straight to mains wall light



Equivalent to 35W halogen

Copper option gradually ages to offer an antique effect

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	No
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	No

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	1.04kg
Inrush Current	5A 0.5ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA

Guarantee

Warranty 1 year

Patent Information

GB2487912 GB2512715

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m
WL170A NW	Black	8W	4000K	18°	472-236	59	1000

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

Accessories

N/A	No accessories required
-----	-------------------------

Beam angle: 18°

