

WL170A

Straight to mains, up / down LED wall light

FEATURES	
IP rating	IP65
CSP Switchable	Single CCT
Tiltable	No
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	No

INSTALLATION IN	IFORMATION
Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	1.04kg
Inrush Current	5A 0.5ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
SELV	Yes

0.1mA

PHOTOMETRICS @ 25°C

Product o	ode	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m
WL170A	NW	Black	8W	4000K	18°	472-236	59	1000

Electric Class (1, 2, 3)

Earth Leakage

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

ACCESSORIES

N/A No accessories required



LIGHTING INNOVATION



Bi-directional, straight to mains wall light



Equivalent to 35W halogen

Copper option gradually ages to offer an antique effect

WARRANTY

Warranty

1 year

PATENT: GB2487912 GB2512715



