

# WL170A

Straight to mains, up / down LED wall light

## FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

# INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	40°C
Weight	1.04kg
Inrush Current	5A 0.5ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1

## PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m
WL170A NW	Black	8W	4000K	18°	472-236	59	1000
For any vertices is a vertice of the LED light source							

Energy rating is a reflection of the LED light source.

# WIRING INFORMATION

Cable / Flying Lead
Type of Wiring Required

#### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

### ACCESSORIES

N/A

No accessories required

0.3m Parallel



LIGHTING INNOVATION



Bi-directional, straight to mains wall light

Equivalent to 35W halogen


Copper option gradually ages to offer an antique effect

#### WARRANTY

anty

1 vear

PATENT: GB2487912 GB2512715



U28mm 60mm 80mm 120mm 100mm