

5.7W

Coastal protected

Adjustable LED fitting

## FEATURES & BENEFITS

Straight to mains

High efficacy of 93lm/W

Improved look and feel with single LED

New stainless steel and anodised bronze finishes

Higher light output than predecessor

Tilts 90° and Rotates 330°



## WL220 MAINS

Straight to mains LED wall light

### FEATURES

<b>IP rating</b>	IP65
<b>CSP Switchable</b>	Single CCT
<b>Tilttable (°)</b>	90
<b>Dimmable Option</b>	No
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3
<b>Rotation angle (°)</b>	330

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	50°C
<b>Weight</b>	WL220B: 500g WL220C: 1200g WL220D: 1000g WL220Z: 500g
<b>Inrush Current</b>	60A 0.037ms
<b>Construction Material</b>	Anodised aluminium, stainless steel 316, copper
<b>UK Bathroom Zone</b>	2
<b>Electric Class (1, 2, 3)</b>	I
<b>Suitable for coastal areas</b>	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL220DWBM40	Stainless steel 316	5.7W	4000K	40°	530	93	1205	
WL220DWBM30	Stainless steel 316	5.7W	3000K	40°	520	91	1182	
WL220ZWBM27	Bronze	5.7W	2700K	40°	515	90	1171	
WL220DWBM27	Stainless steel 316	5.7W	2700K	40°	515	90	1171	
WL220CWBM27	Copper	5.7W	2700K	40°	515	90	1171	

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	0.3m
<b>Type of Wiring Required</b>	Parallel

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A

### ACCESSORIES

<b>GH220</b>	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
<b>GS220</b>	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately

40°