



5.7W



Coastal protected



Adjustable LED fitting

WL220 MAINS

Straight to mains LED wall light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	90°
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	330°

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	50°C
Weight	WL220B: 500g WL220C: 1200g WL220D: 1000g WL220Z: 500g
Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium, stainless steel 316, copper
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Straight to mains
- High efficacy of 93lm/W
- Improved look and feel with single LED
- New stainless steel and anodised bronze finishes
- Higher light output than predecessor
- Tilts 90° and Rotates 330°

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL220DWBM40	Stainless steel 316	5.7W	4000K	40°	530	93	1205	
WL220ZWBM30	Bronze	5.7W	3000K	40°	520	91	1182	
WL220BWBM30	Black	5.7W	3000K	40°	520	91	1182	
WL220DWBM30	Stainless steel 316	5.7W	3000K	40°	520	91	1182	
WL220ZWBM27	Bronze	5.7W	2700K	40°	515	90	1171	
WL220BWBM27	Bronze	5.7W	2700K	40°	515	90	1171	
WL220DWBM27	Stainless steel 316	5.7W	2700K	40°	515	90	1171	
WL220CWBM27	Copper	5.7W	2700K	40°	515	90	1171	

Wiring Information

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

Accessories

GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately

