

WL220 MAINS

Straight to mains LED wall light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tiltable (°)	90
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	330

INSTALLATION INFORMATION

Input	220-240V AC		
Maximum Ambient Temperature	50°C		
	WL220B: 500g WL220C:		
Weight	1200g WL220D: 1000g		
	WL220Z: 500g		
Inrush Current	60A 0.037ms		
Construction Material	Anodised aluminium,		
Construction Material	stainless steel 316, copper		
UK Bathroom Zone	2		
SELV	Yes		
Electric Class (1, 2, 3)	1		
Earth Leakage	0.1		
Suitable for coastal areas	Yes		
Mounting Options	Wall		

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL220DWBM40	Stainless steel 316	5.7W	4000K	40°	530	93	1205	A B E
WL220DWBM30	Stainless steel 316	5.7W	3000K	40°	520	91	1182	A E
WL220ZWBM27	Bronze	5.7W	2700K	40°	515	90	1171	A B B
WL220DWBM27	Stainless steel 316	5.7W	2700K	40°	515	90	1171	A B B
WL220CWBM27	Copper	5.7W	2700K	40°	515	90	1171	A E

WIRING INFORMATION

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	N/A	N/A

ACCESSORIES

GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately



LIGHTING INNOVATION



5.7W



Coastal protected



Adjustable LED fitting

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Straight to mains

High efficacy of 93lm/V

Improved look and feel with single LED

New stainless steel and anodised bronze

finishes

Higher light output than predecessor

Tilts 90° and Rotates 330°

145mm

