

5.7W

Coastal protected

Adjustable LED fitting

FEATURES & BENEFITS

Straight to mains

High efficacy of 93lm/W

Improved look and feel with single LED

New stainless steel and anodised bronze finishes

Higher light output than predecessor

Tilts 90° and Rotates 330°

WL220 MAINS

Straight to mains LED wall light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable (°)	90
Dimmable Option	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	330

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	50°C
Weight	WL220B: 500g WL220C: 1200g WL220D: 1000g WL220Z: 500g
Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium, stainless steel 316, copper
UK Bathroom Zone	2
Electric Class (1, 2, 3)	I
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL220DWBM40	Stainless steel 316	5.7W	4000K	40°	530	93	1205	
WL220DWBM30	Stainless steel 316	5.7W	3000K	40°	520	91	1182	
WL220ZWBM27	Bronze	5.7W	2700K	40°	515	90	1171	
WL220DWBM27	Stainless steel 316	5.7W	2700K	40°	515	90	1171	
WL220CWBM27	Copper	5.7W	2700K	40°	515	90	1171	

WIRING INFORMATION

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A

ACCESSORIES

GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately
GS220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold Separately