



WL240A F



collingwood



Equivalent to 50W halogen



Complete with wall fixings and waterproof crimp connectors



Adjustable angle to direct light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	90°
Dimmable Option	Yes
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	350°

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	0.7kg
Inrush Current	15A 0.5ms
Construction Material	Anodised aluminium
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

Guarantee

Warranty 1 year

Features & benefits

- Cowl design to reduce glare
- Suitable for indoor and outdoor use

Patent Information

GB2487912 GB2512715

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL240A F WW	Silver	8W	3000K	38°	413	52	1168	

Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel


LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (integrated SELV driver)	220-240V	Yes	No	2

Accessories

N/A	No accessories required
-----	-------------------------

Beam angle: 38°



208mm

