

WL339

Asymmetric, straight to mains, cast finish step light

FEATURES

IP rating	IP65
IK rating	N/A
CSP Switchable	Single CCT
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Walk Over / Drive Over	Walk over (Stainless Steel Only)

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	1000g
Inrush Current	9A 0.8ms
Cut Out Size	80
Construction Material	Stainless steel (316)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL339NW	Stainless steel	2.6W	4000K	50°	59	22	65	A F
WL339WW	Stainless steel	2.6W	3000K	50°	50	19	54	A F

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 7mm)		
Type of Wiring Required	Parallel		
Input Cable Type	(H05RN-F) rubberised (OD: 7mm)		

SELV

LED DRIVER

N/A (integrated SELV driver)

Driver

ACCESSORIES		
Installation Tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick release waterproof joint	Sold Separately



LIGHTING INNOVATION





Coastal protected



Main voltage step light

WARRANTY

FEATURES & BENEFITS

Recessed, asymmetric wall or ground light

Ø98mm

