

WL339

Asymmetric, straight to mains, cast finish step light

FEATURES

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	1000g
Inrush Current	9A 0.8ms
Cut Out Size	80
Construction Material	Stainless steel (316)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1
Suitable for coastal areas	Yes

Sold Separately

Sold Separately

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL339WW	Stainless steel	2.6W	3000K	50°	50	19	54	A t G

WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	(H05RN-F) rubberised (OD: 7mm)

LED DRIVER

JB5

WC 5-9

Driver	Input	SELV	Dimming	Bathroom Zone	
N/A (integrated SELV driver)	220-240V	Yes	No	2	
ACCESSORIES					
Installation Tube	For easy ground insta	allation		Included	

Gel filled waterproof connector

Quick release waterproof joint



LIGHTING INNOVATION





Coastal protected



Main voltage step light

WARRANTY

FEATURES & BENEFITS

Recessed, asymmetric wall or ground light

Ø98mm



58/190mm