

# **C** collingwood



2.6W



Coastal protected



Main voltage step light

### **Features**

IP rating	IP65	
IK rating	N/A	
CSP Switchable	Single CCT	
LED Lifetime	L70 70,000h	
Colour Rendering Index	CRI>80	
Colour Consistency	SDCM3	
W. II Q (B : . Q	Walk over (Stainless Steel	
Walk Over / Drive Over	Only)	

## **Installation Information**

Input	220-240V AC
Maximum Ambient Temperature	35°C
Weight	1000g
Inrush Current	9A 0.8ms
Cut Out Size	80
Construction Material	Stainless steel (316)
UK Bathroom Zone	2
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	Yes

### Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
WL339NW	Stainless steel	2.6W	4000K	50°	59	22	65	A F
WL339WW	Stainless steel	2.6W	3000K	50°	50	19	54	A F

# **Wiring Information**

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel
Input Cable Type	(H05RN-F) rubberised (OD: 7mm)

## **LED Driver**

Driver	Input	SELV	Dimming	Bathroom Zone	
N/A (integrated SELV driver)	220-240V	Yes	No	2	

## **Accessories**

Installation Tube	For easy ground installation	Included
JB5	Gel filled waterproof connector	Sold Separately
WC 5-9	Quick release waterproof joint	Sold Separately

## Guarantee

Warranty 7 years

## Features & benefits

- Recessed, asymmetric wall or ground light perfect for illuminating walls, steps and pathways
- Available in rustic cast stainless steel and sleek brushed stainless steel finishes
- Installation tube included



cologgwoodled



ngwoodlighting