

2.6W 2.6W

Coastal protected

AC Main voltage step light

WARRANTY

Warranty 7 years

FEATURES & BENEFITS

Can be used as a wall light or ground light

Installation tube included

1m H05RN-F rubber cable attached for permanent use outdoors

WL342

Asymmetric, straight to mains, brush finish step light

FEATURES

| | |
|------------------------|-------------|
| IP rating | IP65 |
| IK rating | Other |
| CSP Switchable | Single CCT |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |
| Walk Over / Drive Over | Walk over |

INSTALLATION INFORMATION

| | |
|-----------------------------|-------------------------------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 35°C |
| Weight | 1.2Kg |
| Inrush Current | 9A 0.8ms |
| Cut Out Size | 80 |
| Construction Material | Stainless steel (316) antique brass |
| UK Bathroom Zone | 2 |
| SELV | Yes |
| Electric Class (1, 2, 3) | I |
| Earth Leakage | 0.1 |
| Suitable for coastal areas | Yes |

PHOTOMETRICS @ 25°C

| Product code | Finish | Type | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|-----------------|---------------|------|--------|------|----|------|---------|--------|
| WL342NW | Stainless steel | Brushed Steel | 2.6W | 4000K | 50° | 59 | 22 | 65 | A8 F |
| WL342WW | Stainless steel | Brushed Steel | 2.6W | 3000K | 50° | 50 | 19 | 54 | A8 F |
| WL34227 | Stainless steel | Brushed Steel | 2.6W | 2700K | 50° | 49 | 19 | 52 | A8 G |
| WL342AB27 | Antique brass | Antique Brass | 2.6W | 2700K | 50° | 49 | 19 | 52 | A8 G |
| WL342AB30 | Antique brass | Antique Brass | 2.6W | 3000K | 50° | 50 | 19 | 54 | A8 F |

WIRING INFORMATION

| | |
|-------------------------|---|
| Cable / Flying Lead | 1m (H05RN-F) rubberised cable (outside diameter: 7mm) |
| Type of Wiring Required | Parallel |
| Input Cable Type | (H05RN-F) rubberised (OD: 7mm) |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone |
|------------------------------|----------|------|---------|---------------|
| N/A (integrated SELV driver) | 220-240V | Yes | No | 2 |

ACCESSORIES

| | | |
|-------------------|---------------------------------|-----------------|
| Installation Tube | For easy ground installation | Included |
| JB5 | Gel filled waterproof connector | Sold Separately |
| WC 5-9 | Quick release waterproof joint | Sold Separately |

