







CADDY

Colour & wattage switchable multi-purpose bulkhead

FEATURES

IP rating	IP65
IK rating	IK10
CSP Switchable	Switchable CCT
Sensor Option	Yes (on/off and Stepdim)
LED Lifetime	L90 B10 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes, Manual & Self-Test

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C-45°C
Weight	1kg
Inrush Current	14.9mA 252uS
Construction Material	PC
Electric Class (1, 2, 3)	II
Battery	LiFePO4 6.4V 1.5Ah Non-Maintained
UK Building Regulations	Part L
Mounting Options	Ceiling & wall
Power Factor	0.9

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy
WL77WCC	White	On-Off	120°	9W	3000K	1125	125	
					4000K	1150	128	
					6500K	1150	128	
				12W	3000K	1525	127	
					4000K	1550	129	A C G
					6500K	1550	129	
				16W	3000K	2040	128	
					4000K	2080	130	
					6500K	2080	130	
WL77WCCEM	White	Emergency	120°	9W	3000K	1125	125	
					4000K	1150	128	
					6500K	1150	128	
				12W	3000K	1525	127	
					4000K	1550	129	A C G
					6500K	1550	129	
				16W	3000K	2040	128	
					4000K	2080	130	
					6500K	2080	130	

ACCESSORIES

WL77KITMS	Caddy Plug-in Kit, Microwave Sensor Master Slave	Sold Separately
WL77KITSD	Caddy Plug-in Kit, Microwave Sensor Step Dim	Sold Separately
WL77WE	Caddy White Eyelid	Sold Separately
ACREMOTEMWS	Optional Remote control for Step-Dim Sensor	Sold Separately

COLLINGWOOD
LIGHTING

LIGHTING INNOVATION

IP65 IP65 suitable for use outside

IK10 IK10

Wattage & CCT Switchable

WARRANTY

Warranty	5 years
Battery Warranty	3 years
On-Site Warranty	2 years

FEATURES & BENEFITS

- Slim depth of just 78mm
- Sensor Live-out terminal for master slave operation.
- 4-way conduit entry points & BESA
- Plug and play sensors to accommodate project requirements.
- Hinged gear tray for ease of installation.
- High efficacy, up to 130lm/W
- Anti-tamper mechanism built into diffuser.
- Emergency luminiare with dual manual & self test capability - select via switch.



