



CCT switchable between 3000K, 4000K & 6500K

Quick and easy installation bracket

Emergency option available

WL94

IP44 LED Bulkhead

Features

IP rating	IP44
IK rating	IK07
CSP Switchable	Switchable CCT
Sensor Option	Microwave (Step-Dim)
Dimmable Option	No
LED Lifetime	L70 35,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	No

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	830g
Inrush Current	9.8A 50ms
Construction Material	Polycarbonate galvanized steel bracket
UK Bathroom Zone	2
Electric Class (1, 2, 3)	2
Install Connector Type	4 ways, push-fit
Mounting Options	Ceiling & wall
Power Factor	0.5

Guarantee

Warranty 3 years

Features & benefits

- High efficacy of 111lm/W
- IP44 rating: suitable for use in kitchens and bathrooms.
- Diffuser design makes a halo effect on the wall or ceiling
- Easy access push fit terminals
- Innovative clip-on bracket design
- Straight to mains
- Microwave step-dim dusk-down sensor, which is programmable by dip switches, saving energy by having it on only when needed
- Flicker free, resulting in a more comfortable setting

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	lx@1m	EM lm	Energy
WL9410SCS	White	Standard	120°	10W	3000K	1000	100	288	-	
					4000K	1100	110	317	-	
					6500K	1100	110	317	-	
WL9410ECS	White	Emergency	120°	10W	3000K	1000	100	288	220	
					4000K	1100	110	317	220	
					6500K	1100	110	317	220	
WL9410MCS	White	Microwave sensor	120°	10W	3000K	1000	100	288	-	
					4000K	1100	110	317	-	
					6500K	1100	110	317	-	
WL9410CCS	White	Emergency Microwave sensor	120°	10W	3000K	1000	100	288	220	
					4000K	1100	110	317	220	
					6500K	1100	110	317	220	
WL9418SCS	White	Standard	120°	18W	3000K	1800	100	518	-	
					4000K	2000	111	576	-	
					6500K	2000	111	576	-	
WL9418ECS	White	Emergency	120°	18W	3000K	1800	100	518	220	
					4000K	2000	111	576	220	
					6500K	2000	111	576	220	
WL9418MCS	White	Microwave sensor	120°	18W	3000K	1800	100	518	-	
					4000K	2000	111	576	-	
					6500K	2000	111	576	-	
WL9418CCS	White	Emergency Microwave sensor	120°	18W	3000K	1800	100	518	220	
					4000K	2000	111	576	220	
					6500K	2000	111	576	220	

Wiring Information

Cable / Flying Lead	Push-fit terminals 1.5mm ² max.
Type of Wiring Required	Parallel

Accessories

N/A	No accessories required	Sold Separately
-----	-------------------------	-----------------

