

 CCT switchable between 3000K, 4000K & 6500K

 Wattage switchable between 10W & 15W

 Emergency option available

WL95

IP65 10-15W Wattage and Colour Switchable Bulkhead

Features

IP rating	IP65
IK rating	IK10
CSP Switchable	Switchable CCT
Sensor Option	Microwave (Step-Dim)
Dimmable Option	No
LED Lifetime	L70 35,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Emergency Option	Yes

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	850g
Inrush Current	10A 50ms
Construction Material	ABS housing PC diffuser
UK Bathroom Zone	2
Electric Class (1, 2, 3)	2
Install Connector Type	4 ways, push-fit
Mounting Options	Ceiling & wall
Power Factor	0.9








Guarantee


Warranty 3 years

Features & benefits


- Slimline design
- Multiple mounting options: BESA box, M20 conduit, cable glands
- IP65 rated, making it perfect for using outdoors
- High efficacy of 120lm/W
- Multiple black bezel options available
- Easy access push fit screwless terminals
- Microwave step-dim dusk-down sensor, which is programmable by dip switches, saving energy by having it on only when needed
- Flicker free, resulting in a more comfortable setting

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	lx@1m	EM lm	Energy
WL9515SCS	White	Standard	115°	10W	3000K	1100	110	364	-	
					4000K	1200	120	397	-	
					6500K	1200	120	397	-	
				15W	3000K	1650	110	364	-	
					4000K	1800	120	397	-	
					6500K	1800	120	397	-	
WL9515MCS	White	Microwave sensor	115°	10W	3000K	1100	110	364	-	
					4000K	1200	120	397	-	
					6500K	1200	120	397	-	
				15W	3000K	1650	110	364	-	
					4000K	1800	120	397	-	
					6500K	1800	120	397	-	
WL9515ECS	White	Emergency	115°	10W	3000K	1100	110	364	120	
					4000K	1200	120	397	120	
					6500K	1200	120	397	120	
				15W	3000K	1650	110	364	120	
					4000K	1800	120	397	120	
					6500K	1800	120	397	120	
WL9515CCS	White	Emergency Microwave sensor	115°	10W	3000K	1100	110	364	120	
					4000K	1200	120	397	120	
					6500K	1200	120	397	120	
				15W	3000K	1650	110	364	120	
					4000K	1800	120	397	120	
					6500K	1800	120	397	120	
WL9515SCSB	Black	Standard	115°	10W	3000K	1100	110	364	-	
					4000K	1200	120	397	-	
					6500K	1200	120	397	-	
				15W	3000K	1650	110	364	-	
					4000K	1800	120	397	-	
					6500K	1800	120	397	-	
WL9515ECSB	Black	Emergency	115°	10W	3000K	1100	110	364	120	
					4000K	1200	120	397	120	
					6500K	1200	120	397	120	
				15W	3000K	1650	110	364	120	
					4000K	1800	120	397	120	
					6500K	1800	120	397	120	
WL9515MCSB	Black	Microwave sensor	115°	10W	3000K	1100	110	364	-	
					4000K	1200	120	397	-	
					6500K	1200	120	397	-	



Bulkheads specification sheet

WL95I5CCSB	Black	Emergency Microwave sensor	115°	15W	3000K	1650	110	364	-					
					4000K	1800	120	397	-					
					6500K	1800	120	397	-					
				10W	3000K	1100	110	364	120					
					4000K	1200	120	397	120					
					6500K	1200	120	397	120					
				15W	3000K	1650	110	364	120					
					4000K	1800	120	397	120					
								6500K	1800		120	397	120	



Bulkheads are a simple yet functional product that offer a practical solution for lighting commercial spaces, corridors and stairways, as well as indoor and outdoor communal spaces. With a high efficacy and a choice of two lumen levels, this easy install, colour switchable light is a robust and durable option.

Wiring Information

Cable / Flying Lead	Push-fit terminals, 1.5mm ² max, loop-in/loop-out.
Type of Wiring Required	Parallel

Accessories

WL95BEW	White Eyelid Accessory	Sold Separately
---------	------------------------	-----------------