



## WL95 Versa

CCT Colour & Wattage Switchable Bulkhead with plug-in Versabox accessories

### Features

IP rating	IP65
IK rating	IK09
CSP Switchable	Switchable CCT
Sensor Option	Microwave + Photocell options
Dimmable Option	Yes (DALI-2)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, Manual, Self and DALI-2 Test

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	0.6 - 0.9kg
Inrush Current	8W: 17A 0.42ms, 20W: 19A 0.46ms
Construction Material	ABS Housing (RAL9003 or 9005), Anti-UV Diffuser, 850°, RGI
UK Bathroom Zone	2
Electric Class (1, 2, 3)	2
Install Connector Type	Push-fit terminal, loop-in/loop-out
UK Building Regulations	Part L
Mounting Options	Ceiling & wall
Power Factor	0.9

### Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy
WL95W2NCS	White	250mm On-Off	115°	5W	3000K	700	140	AIG C
					4000K	750	150	
					6000K	750	150	
				6.5W	3000K	950	146	
					4000K	1000	154	
					6000K	1000	154	
					3000K	1200	150	
					4000K	1250	156	
					6000K	1250	156	
					3000K	1450	145	
8W	4000K	1500	150					
	6000K	1500	150					
	3000K	2100	140					
	4000K	2200	147					
	6000K	2200	147					
	3000K	2800	140					
WL95W3NCS	White	300mm On-Off	115°	10W	4000K	1500	150	AIG C
					6000K	1500	150	
					3000K	2100	140	
				15W	4000K	2200	147	
					6000K	2200	147	
					3000K	2800	140	
				20W	4000K	3000	150	
					6000K	3000	150	
					3000K	700	140	
					4000K	750	150	
WL95W2DCS	White	250mm DALI-2	115°	5W	4000K	750	150	AIG C
					6000K	750	150	
					3000K	950	146	
				6.5W	4000K	1000	154	
					6000K	1000	154	
					3000K	1200	150	
					4000K	1250	156	
					6000K	1250	156	
					3000K	1450	140	
					4000K	1500	150	
8W	6000K	1500	150					
	3000K	2100	140					
	4000K	2200	147					
	6000K	2200	147					
	3000K	2800	140					
	4000K	3000	150					
WL95W3DCS	White	300mm DALI-2	115°	10W	3000K	1450	140	AIG C
					4000K	1500	150	
					6000K	1500	150	
				15W	3000K	2100	140	
					4000K	2200	147	
					6000K	2200	147	
				20W	3000K	2800	140	
					4000K	3000	150	
					6000K	3000	150	
					3000K	2800	140	



CCT switchable between 3000K, 4000K & 6000K

Wattage switchable options from 5W to 20W

IK09 for impact protection



### Guarantee

Warranty	5 years
Battery Warranty	5 years
On-Site Warranty	2 years

### Features & benefits

- IP65 suitable for use outside under a canopy
- Slim depth of just 80mm
- Ultra efficient up to 154 lm/W for fast paybacks
- 4-way conduit entry points
- Detachable terminal block for convenient wiring
- Modular design for tool-less installation
- Versabox plug and play kit range to accommodate project requirements

Beam angle: 115°





collingwood

WL95 Versa is the ultimate bulkhead, with CCT adjustable from warm 3000K to bright 6000K and wattage options ranging from 5W to 20W, all packed in a slim, impact-resistant (IK09) and weatherproof (IP65) design. Plus with high efficiency of up to 154lm/W. This bulkhead offers easy installation with 4-way conduit entry, detachable terminal block, and tool-less modular design, and is compatible with Versabox plug-and-play kits for ultimate project customization.

Model	Color	Mounting	Beam Angle	Wattage	3000K	4000K	6000K	Notes						
WL95B2NCS	Black	250mm On-Off	115°	5W	4000K	3000	150							
					6000K	3000	150							
				6.5W	3000K	700	140							
					4000K	750	150							
					6000K	750	150							
					3000K	950	146							
					4000K	1000	154							
					6000K	1000	154							
				8W	3000K	1200	150							
					4000K	1250	156							
6000K	1250	156												
3000K	1450	145												
WL95B3NCS	Black	300mm On-Off	115°	10W	4000K	1500	150							
					6000K	1500	150							
				15W	3000K	2100	140							
					4000K	2200	147							
					6000K	2200	147							
					3000K	2800	140							
				20W	4000K	3000	150							
					6000K	3000	150							
				WL95B2DCS	Black	250mm DALI-2	115°		5W	3000K	700	140		
										4000K	750	150		
6.5W	6000K	750	150											
	3000K	950	146											
	4000K	1000	154											
	6000K	1000	154											
	3000K	1200	150											
	4000K	1250	156											
8W	6000K	1250	156											
	3000K	1450	140											
	4000K	1500	150											
	6000K	1500	150											
WL95B3DCS	Black	300mm DALI-2	115°	10W	3000K	2100	140							
					4000K	2200	147							
				15W	6000K	2200	147							
					3000K	2800	140							
					4000K	3000	150							
					6000K	3000	150							
				20W	2700K	750	150							
					3000K	1000	150							
				WL95W2NEMCS	White	250mm On-Off Manual Emergency	115°		5W	4000K	1200	150		
										2700K	750	150		
8W	3000K	1000	150											
	4000K	1200	150											
	WL95W3NEMCS	White	300mm On-Off Manual Emergency					115°	10W	2700K	1500	160		
										3000K	2200	160		

## Wiring Information

Cable / Flying Lead	Push-fit terminals, 2.5mm <sup>2</sup> max, loop-in/loop-out.
Type of Wiring Required	Parallel

## Accessories

WLKITMANEM	Manual Test Emergency plug-in Versabox, 250lm	Sold Separately
WLKITSELFEM	Self Test Emergency plug-in Versabox, 250lm	Sold Separately
WLKITPC	Photocell plug-in Versabox	Sold Separately
WLKITMWS	Microwave Sensor on/off plug-in Versabox	Sold Separately
UNREMOEMWS	Remote control for use with microwave sensor	Sold Separately
WL95BEW	White Eyelid Accessory (300mm only)	Sold Separately
WL95BE	Black Eyelid Accessory (300mm only)	Sold Separately