



CCT switchable between 3000K, 4000K & 6000K



Wattage switchable options from 5W to 20W



IK09 for impact protection

WARRANTY

Warranty	5 years
Battery Warranty	5 years
On-Site Warranty	2 years

FEATURES & BENEFITS

- IP65 suitable for use outside under a canopy
- Slim depth of just 80mm
- Ultra efficient up to 156 lm/W for fast paybacks
- 4-way conduit entry points & BESA
- Detachable terminal block for convenient wiring
- Modular design for tool-less installation
- Versabox plug and play kit range to accommodate project requirements
- WLKITMWS microwave sensor is commissioned with a remote control to aid easy adjustment of settings once installation is complete. Use UNREMOEMWS.



Black eyelid
WL95BE
300mm only



White eyelid
WL95BEW
300mm only

WL95 VERSA

CCT Colour & Wattage Switchable Bulkhead with plug-in Versabox accessories

FEATURES

IP rating	IP65
IK rating	IK09
CSP Switchable	Switchable CCT
Sensor Option	Microwave + Photocell options
Dimmable Option	Yes (DALI-2, PUSH-DIM)
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM4
Emergency Option	Yes, Manual, Self and DALI-2 Test



INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	0.6 - 0.9kg
Inrush Current	8W: 17A 0.42ms, 20W: 19A 0.46ms
Construction Material	ABS Housing (RAL9003), Anti-UV Diffuser, 850°
UK Bathroom Zone	2
Electric Class (1, 2, 3)	II
Install Connector Type	Push-fit terminal, loop-in/loop-out
UK Building Regulations	Part L
Mounting Options	Ceiling & wall
Power Factor	0.9

Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy					
WL95W3DEDCS	White	300mm DALI-2 Emergency	115°	10W	6000K	1500	150	A t G C					
					3000K	2100	140						
				15W	4000K	2200	147						
					6000K	2200	147						
				20W	3000K	2800	140						
					4000K	3000	150						
WL95W2NMECS	White	250mm On-Off Microwave Self Test Emergency	115°	5W	3000K	700	140	A t G C					
					4000K	750	150						
				6.5W	6000K	750	150						
					3000K	950	146						
				8W	4000K	1000	154						
					6000K	1000	154						
				WL95W3NMECS	White	300mm On-Off Microwave Self Test Emergency	115°		10W	3000K	1200	150	A t G C
										4000K	1250	156	
									15W	6000K	1250	156	
										3000K	1450	140	
									20W	4000K	1500	150	
										6000K	1500	150	

BEAM ANGLE: 115°




LIGHTING INNOVATION

WL95 Versa is the ultimate bulkhead, with CCT adjustable from warm 3000K to bright 6000K and wattage options ranging from 5W to 20W, all packed in a slim, impact-resistant (IK09) and weatherproof (IP65) design. Plus with high efficiency of up to 154lm/W. This bulkhead offers easy installation with 4-way conduit entry, detachable terminal block, and tool-less modular design, and is compatible with Versabox plug-and-play kits for ultimate project customization.

Model	Color	Control	Beam Angle	Wattage	3000K	4000K	6000K	Notes	
WL95W2NPCS	White	250mm On-Off Photocell	115°	5W	3000K	700	140		
					4000K	750	150		
					6000K	750	150		
				6.5W	3000K	950	146		
					4000K	1000	154		
					6000K	1000	154		
					8W	3000K	1200	150	
						4000K	1250	156	
						6000K	1250	156	
WL95W3NPCS	White	300mm On-Off Photocell	115°	10W	3000K	1450	140		
					4000K	1500	150		
					6000K	1500	150		
				15W	3000K	2100	140		
					4000K	2200	147	At G C	
					6000K	2200	147		
					20W	3000K	2800	140	
						4000K	3000	150	
						6000K	3000	150	
WL95W2NPEMCS	White	250mm On-Off Photocell Manual Emergency	115°	5W	3000K	700	140		
					4000K	750	150		
					6000K	750	150		
				6.5W	3000K	950	146		
					4000K	1000	154	At G C	
					6000K	1000	154		
					8W	3000K	1200	150	
						4000K	1250	156	
						6000K	1250	156	
WL95W3NPEMCS	White	300mm On-Off Photocell Manual Emergency	115°	10W	3000K	1450	140		
					4000K	1500	150		
					6000K	1500	150		
				15W	3000K	2100	140		
					4000K	2200	147	At G C	
					6000K	2200	147		
					20W	3000K	2800	140	
						4000K	3000	150	
						6000K	3000	150	
WL95B2NECS	Black	250mm On-Off Self Test Emergency	115°	5W	3000K	700	140		
					4000K	750	150		
					6000K	750	150		
				6.5W	3000K	950	146		
					4000K	1000	154	At G C	
					6000K	1000	154		
					8W	3000K	1200	150	
						4000K	1250	156	
						6000K	1250	156	
WL95B3NECS	Black	300mm On-Off Self Test Emergency	115°	10W	3000K	1450	140		
					4000K	1500	150		
					6000K	1500	150		
				15W	3000K	2100	140		
					4000K	2200	147	At G C	
					6000K	2200	147		
					20W	3000K	2800	140	
						4000K	3000	150	
						6000K	3000	150	

Default Settings: 4000K colour temperature, 20W power consumption. Energy rating is a reflection of the LED light source.

WL95B3DEDCS	Black	300mm DALI-2	115°	10W	3000K	1450	140	
		Emergency						

WIRING INFORMATION

Cable / Flying Lead	Push-fit terminals, 2.5mm ² max, loop-in/loop-out.
Type of Wiring Required	Parallel

ACCESSORIES

WLKITMANEM	Manual Test Emergency plug-in Versabox, 250lm	Sold Separately
WLKITSELFEM	Self Test Emergency plug-in Versabox, 250lm	Sold Separately
WLKITPC	Photocell plug-in Versabox (must be used with UNREMOTEMWS)	Sold Separately
WLKITMWS	Microwave Sensor on/off plug-in Versabox (must be used with UNREMOTEMWS)	Sold Separately
UNREMOTEMWS	Remote control for use with microwave sensor	Sold Separately
WL95BEW	White Eyelid Accessory (300mm only)	Sold Separately
WL95BE	Black Eyelid Accessory (300mm only)	Sold Separately



COLLINGWOOD
LIGHTING

LIGHTING INNOVATION

WL95 Versa is the ultimate bulkhead, with CCT adjustable from warm 3000K to bright 6000K and wattage options ranging from 5W to 20W, all packed in a slim, impact-resistant (IK09) and weatherproof (IP65) design. Plus with high efficiency of up to 154lm/W. This bulkhead offers easy installation with 4-way conduit entry, detachable terminal block, and tool-less modular design, and is compatible with Versabox plug-and-play kits for ultimate project customization.