



Adler



Part of the Emergency product category



Model	Adler Exit Box Maintained / Non-Maintained Black
Code	AADLSE/BLK
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	2W
Operating Temp	5°C - 40°C
CCT	6500K

MATERIAL INFORMATION

Main Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.861 kg
Colour / Finish	Black
Height	179 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	6
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Wall
Power Factor	0.39
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Rotatable legends to reduce waste and increase flexibility
- Rotatable legends to reduce waste and increase flexibility
- LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime
- Selectable self-test/manual test as standard.
- 20mm side cable entries, plus rear BESA mounting





Adler



Part of the Emergency product category

Model	Adler Exit Box Maintained / Non-Maintained Black
Code	AADLSE/BLK
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Retail

