



Astro

Astro CCT 1 Corridor Function Black Code: AALED1/BV/CCT/CF




industrial applications

4000K

performance





Category


Application

Specification

Bulkheads

Architectural

Industrial, Outdoor



Ancillary, Commercial, Education, Healthcare,

PRODUCT FEATURES

- Push fit feed-in, feed-out terminals for speed and ease of installation
 - Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
 - · Instant light output and unlimited switching

| GENERAL INFORMATION | | |
|----------------------------------|-----------------------|--|
| Wattage | 8.5W | |
| Lumens Delivered | 620lm - 1000lm(4000K) | |
| Lm/W | 140lm/W(4000K) | |
| Beam Angle | 115 | |
| CRI | 80 | |
| ССТ | 3000/4000K | |
| Input | 220-240V | |
| Operating Temp | -10°C - 40°C | |
| SDCM | 3 | |
| Product Weight without Packaging | 0.602 kg | |
| | | |

All polycarbonate multi-purpose LED square bulkhead suitable for ancillary areas and

• Internal CCT selector switch allows the installer to choose the CCT between 3000K and

Unique Visiluxe diffuser allows 90% light transmission from LED source for increased

| TECHNICAL INFORMATION | | |
|--------------------------------|---------------------|--|
| Light Source | LED | |
| Colour / Finish | Black / Visiluxe | |
| IP Rating | IP65 | |
| Class Protection | 2 | |
| Internal / External | Internal / External | |
| Surface / Recessed / Suspended | Ceiling, Wall | |
| Lumen Depreciation | L80 60,000h | |
| Warranty (Years) | 5 | |
| CE Mark | Yes | |
| | fes | |

