





@ansell\_lighting






in Ansell Lighting




## **Astro**


## Astro CCT 2 Corridor Function Self-test Emergency Code: AALED2/BV/CCT/CF/SM3











## PRODUCT FEATURES

- All polycarbonate multi-purpose LED square bulkhead suitable for ancillary areas and industrial applications
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- Push fit feed-in, feed-out terminals for speed and ease of installation
- Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
- · Instant light output and unlimited switching

GENERAL INFORMATION	
Wattage	14.5W
Lumens Delivered	1000lm - 1700lm(4000K)
Lm/W	140lm/W(4000K)
Beam Angle	115
CRI	80
CCT	3000/4000/5700K
Input	220-240V
Operating Temp	5°C - 40°C
SDCM	3
Product Weight without Packaging	1.141 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	Black / Visiluxe
IP Rating	IP65
Class Protection	2
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Lumen Depreciation	L80 60,000h
Warranty (Years)	5
CE Mark	Yes