Apex

Part of the Commercial Linear product category

Model	Apex Tubular 1200mm Self Test Emergency
Code	AAPE4/1/SM3
Application	Industrial

GENERAL INFORMATION

Input	220-240V
Wattage	36W
Operating Temp	-20°C to 40°C
Lumens Delivered	5760lm
lm/W	160lm/W
CCT	4000K
Beam Angle	117

MATERIAL INFORMATION

Main Material	Stainless Steel 316 & PMMA
Diffuser Material	PMMA
Product Weight without Packaging	1.432 kg
Colour / Finish	White
Diameter	70 mm
Height	72 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Suspended
Power Factor	0.9
L70 @ 25°C	L80B50 71000hrs

PRODUCT FEATURES

- Industrial IP69K tubular surface or suspended Ideal for harsh applications such as garages, food industry, chemical plants and agriculture
- IP69K rating allows cleaning with high pressure and high temperature water
- 316 Marine grade stainless steel end caps and fixings
- PMMA IK06 body, resistant to mechanical stress
- Quick and easy electrical connection without opening the luminaire

ACCESSORIES

AAPE/SK/1	Apex Tubular Suspension Kit





Apex

Part of the Commercial Linear product category

Model	Apex Tubular 1200mm Self Test Emergency
Code	AAPE4/1/SM3
Application	Industrial













