






ARX Bulkhead

ARX Anti-Ligature Bulkhead CCT White Switch Dim
Code: AARXB/1/DD1/SM3

| | |
|---------------|--|
| Category | Bulkheads |
| Application | Commercial, Healthcare, Hospitality, Industrial, Outdoor |
| Specification | Performance |



PRODUCT FEATURES

- IP65 IK10 CCT polycarbonate luminaire suitable for healthcare and educational applications
- IK10 polycarbonate construction ensures maximum strength and durability
- Anti-tamper screws prevent vandalism or removal of bezel with standard tools
- Corridor function options available for effective reduction in energy consumption
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs in one luminaire
- Deep bezel design mounts flush with installation surface, not allowing access to the rear of the fitting without first removing the bezel
- Clip in gear tray ensures quick installation
- Dimmable, MWS and Emergency options available

| GENERAL INFORMATION | |
|----------------------------------|---------------------------|
| Wattage | 10.5W - 18W |
| Lumens Delivered | 1300lm - 2200lm (4000K) |
| Lm/W | 130lm/W - 120lm/W (4000K) |
| Beam Angle | 110 |
| CRI | 80 |
| CCT | 3000/4000K |
| Input | 220/240V |
| Operating Temp | 0°C - 40°C |
| SDCM | 6 |
| Energy efficiency class | C |
| Product Weight without Packaging | 1.21 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|---------------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP65 |
| Class Protection | 2 |
| Internal / External | Internal / External |
| Surface / Recessed / Suspended | Ceiling, Wall |
| Lumen Depreciation | L80 90,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Diameter | 350 mm |
| Height | 110 mm |

