






ARX Bulkhead

ARX Anti-Ligature Bulkhead CCT White DALI Self-Code: AARXB/1/DD3/SM3

Category	Bulkheads
Application	Commercial, Healthcare, Hospitality, Industrial, Outdoor
Specification	Performance



PRODUCT FEATURES

- IP65 IK10 CCT polycarbonate luminaire suitable for healthcare and educational applications
- IK10 polycarbonate construction ensures maximum strength and durability
- Anti-tamper screws prevent vandalism or removal of bezel with standard tools
- Corridor function options available for effective reduction in energy consumption
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs in one luminaire
- Deep bezel design mounts flush with installation surface, not allowing access to the rear of the fitting without first removing the bezel
- Clip in gear tray ensures quick installation
- Dimmable, MWS and Emergency options available

GENERAL INFORMATION	
Wattage	10.5W - 18W
Lumens Delivered	1300lm - 2200lm (4000K)
Lm/W	130lm/W - 120lm/W (4000K)
Beam Angle	110
CRI	80
CCT	3000/4000K
Input	220/240V
Operating Temp	0°C - 40°C
SDCM	6
Energy efficiency class	C

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP65
Class Protection	2
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Lumen Depreciation	L80 90,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	350 mm
Height	110 mm

