






# ARX Bulkhead

ARX Anti-Ligature Bulkhead CCT White DALI Self-Code: AARXB/1/DD3/SM3

|               |  |
|---------------|--|
| Category      | Bulkheads  |
| Application   | Commercial, Healthcare, Hospitality, Industrial, Outdoor |
| Specification | Performance  |



## PRODUCT FEATURES

- IP65 IK10 CCT polycarbonate luminaire suitable for healthcare and educational applications
- IK10 polycarbonate construction ensures maximum strength and durability
- Anti-tamper screws prevent vandalism or removal of bezel with standard tools
- Corridor function options available for effective reduction in energy consumption
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs in one luminaire
- Deep bezel design mounts flush with installation surface, not allowing access to the rear of the fitting without first removing the bezel
- Clip in gear tray ensures quick installation
- Dimmable, MWS and Emergency options available

| GENERAL INFORMATION     |                           |
|-------------------------|---------------------------|
| Wattage                 | 10.5W - 18W               |
| Lumens Delivered        | 1300lm - 2200lm (4000K)   |
| Lm/W                    | 130lm/W - 120lm/W (4000K) |
| Beam Angle              | 110                       |
| CRI                     | 80                        |
| CCT                     | 3000/4000K                |
| Input                   | 220-240V                  |
| Operating Temp          | 0°C - 40°C                |
| SDCM                    | 6                         |
| Energy efficiency class | C                         |

| TECHNICAL INFORMATION          |                     |
|--------------------------------|---------------------|
| Light Source                   | LED                 |
| Colour / Finish                | White               |
| IP Rating                      | IP65                |
| Class Protection               | 2                   |
| Internal / External            | Internal / External |
| Surface / Recessed / Suspended | Ceiling, Wall       |
| Lumen Depreciation             | L80 90,000h         |
| Warranty (Years)               | 5                   |
| CE Mark                        | Yes                 |
| Diameter                       | 350 mm              |
| Height                         | 110 mm              |

