Avio

Part of the Bollards product category

Model	Avio Bollard Black Self-Test Emergency
Code	AAVIO/1/BK/SM3
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	6W - 24W
Operating Temp	-30°C - 50°C
Lumens Delivered	570lm - 2200lm (4000K)
lm/W	95lm/W (4000K)
CCT	3000K/4000K
Beam Angle	140

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	5.13 kg
Colour / Finish	Black
Diameter	170 mm
Height	930 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Floor
Power Factor	0.97
L70 @ 25°C	L70 60,000h

PRODUCT FEATURES

- Robust die-cast aluminium bollard with a choice of textured finishes suitable for commercial applications
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 4 outputs, in one luminaire
- Half-shield lens option to offer single direction output
- Precision-engineered lensed optic delivers exceptional light distribution and performance, ensuring maximum efficiency and visual comfort
- Removable head design allows easy access to the integrated CCT and wattage switches, seamlessly housed within the head for quick adjustments and enhanced convenience during installation or maintenance

ACCESSORIES

AAVIO/HS/BK	Avio Bollard Half Shield Black
ARMKIT/1	Bollard Root Mounting Kit





Avio

Part of the Bollards product category

Model	Avio Bollard Black Self-Test Emergency
Code	AAVIO/1/BK/SM3
Application	Commercial, Education, Healthcare, Hospitality, Industrial, Retail











