



Application	Commercial, Education, Healthcare, Hospitality, Industrial, Retail	
Specification	Architectural	

## **Avio**

Avio Bollard Black Self-Test Emergency Code: AAVIO/1/BK/SM3







## **PRODUCT FEATURES**

- Robust die-cast aluminium bollard with a choice of textured finishes suitable for commercial applications
- Half-shield lens option to offer single direction output
- Removable head design allows easy access to the integrated CCT and wattage switches, seamlessly housed within the head for quick adjustments and enhanced convenience during installation or maintenance
- Supplied c/w base plate, root mounting kit accessory available

- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 4 outputs, in one luminaire
- Precision-engineered lensed optic delivers exceptional light distribution and performance, ensuring maximum efficiency and visual comfort
- Comes complete with a AFIX connector (AFIXIP/1/SC/3C) for quick and easy IP rated connection

GENERAL INFORMATION		
Wattage	6W - 24W	
Lumens Delivered	570lm - 2200lm (4000K)	
Lm/W	95lm/W (4000K)	
Beam Angle	140	
CRI	80	
CCT	3000K/4000K	
Input	220-240V	
Operating Temp	-30°C - 50°C	
SDCM	5	
Product Weight without Packaging	5.13 kg	

TECHNICAL	INFORMATION		
TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Black		
IP Rating	IP66		
IK Rating	IK08		
Class Protection	1		
Internal / External	External		
Surface / Recessed / Suspended	Floor		
Lumen Depreciation	L80 60,000h		
Warranty (Years)	5		
CE Mark	Yes		
Diameter	170 mm		
Height	930 mm		











Application	Commercial, Education, Healthcare, Hospitality,	
	Industrial, Retail	
Specification	Architectural	

## **Avio**

Avio Bollard Black Self-Test Emergency Code: AAVIO/1/BK/SM3





ACCESSORIES		
AAVIO/HS/BK	Avio Bollard Half Shield Black	
ARMKIT/1	Bollard Root Mounting Kit	







Belfast: +44 (0) 2890 773750 www.ansell-lighting.com Warrington: +44 (0) 1942 433333

