



@ansell\_lighting



ansellighting



Ansell Lighting





ansell\_lighting

# Aztec Coastal Asymmetric

Aztec Coastal Asymmetrical Floodlight 300W

Code: AAZCLED300/ASY

|               |  |
|---------------|--|
| Category      | Floodlights  |
| Application   | Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail |
| Specification | Performance  |



## PRODUCT FEATURES

- High performance die-cast marine grade aluminium LED floodlight suitable for industrial and coastal applications
- Marine grade construction ideal for coastal and adverse weather, swimming pool and chemical plant applications
- Pre-installed breathable gland prevents internal moisture accumulation
- Concentrated saline 3,000 hour salt spray test to EN ISO 9227
- 304L stainless steel mounting bracket and fixings
- High output, high efficiency asymmetric lens technology for anti-light pollution
- Pre-wired with 1.5 metre of rubber insulated cable for ease of installation
- High purity aluminium construction, surface electrophoresis and corrosion-proof treatment

## GENERAL INFORMATION

|                                  |              |
|----------------------------------|--------------|
| Wattage                          | 300W         |
| Lumens Delivered                 | 42500lm      |
| Lm/W                             | 142lm/W      |
| Beam Angle                       | 60/120       |
| CRI                              | 70           |
| CCT                              | 5000K        |
| Input                            | 220-240V     |
| Operating Temp                   | -30°C - 50°C |
| SDCM                             | 5            |
| Product Weight without Packaging | 7.87 kg      |

## TECHNICAL INFORMATION

|                                |             |
|--------------------------------|-------------|
| Light Source                   | LED         |
| Colour / Finish                | Aluminium   |
| IP Rating                      | IP66        |
| Class Protection               | 1           |
| Internal / External            | External    |
| Surface / Recessed / Suspended | Pole, Wall  |
| Lumen Depreciation             | L80 54,000h |
| Warranty (Years)               | 5           |
| CE Mark                        | Yes         |
| Height                         | 470 mm      |

