





Floodlights

Performance



Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail








Aztec Symmetrical

Aztec Symmetrical Floodlight 150W Photocell Code: AAZLED150/PC





Category

Application

Specification



PRODUCT FEATURES

- High performance die-cast aluminium LED floodlight with symmetrical light distribution suitable for industrial applications
- Pre-installed breathable gland prevents internal moisture accumulation
- · High efficiency up to 148 Lm/W

www.ansell-lighting.com

• Non-dimmable

- High output, high efficiency floodlight
- Bracket design allows installation without removing mounting bracket
- Pre-wired with 1.5 metre of rubber insulated cable for ease of installation

GENERAL INFORMATION		
Wattage	150W	
Lumens Delivered	21800lm	
Lm/W	145lm/W	
Beam Angle	115	
CRI	70	
ССТ	5000K	
Input	220-240V	
Operating Temp	-30°C - 40°C	
SDCM	5	
Product Weight without Packaging	4.12 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP66	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Pole, Wall	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	360 mm	