





Floodlights

Performance








Aztec Asymmetric

Aztec Asymmetrical Floodlight 200W Photocell Code: AAZLED200/ASY/PC

200W



Category

Application

Specification



Ancillary, Commercial, Education, Healthcare, Hospitality, Industrial, Outdoor, Retail

PRODUCT FEATURES

- High performance die-cast aluminium LED floodlight suitable for industrial applications
- Pre-installed breathable gland prevents internal moisture accumulation
- High efficiency up to 143 Lm/W
- Non-dimmable

- High output, high efficiency asymmetric lens technology for anti-light pollution
- Bracket design allows installation without removing mounting bracket
- Pre-wired with 1.5 metre of rubber insulated cable for ease of installation

GENERAL INFORMATION		
Wattage	200W	
Lumens Delivered	28000lm	
Lm/W	141lm/W	
Beam Angle	60/120	
CRI	70	
CCT	5000K	
Input	220-240V	
Operating Temp	-30°C - 40°C	
SDCM	5	
Product Weight without Packaging	5.272 kg	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Black	
IP Rating	IP66	
Class Protection	1	
Internal / External	External	
Surface / Recessed / Suspended	Pole, Wall	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	398 mm	

