



| Category | Floodlights | |
|---------------|---|--|
| Application | Ancillary, Commercial, Education, Healthcare, | |
| | Hospitality, Industrial, Outdoor, Retail | |
| Specification | Performance | |

Aztec Symmetrical

Aztec Symmetrical Floodlight 50W

Code: AAZLED50



PRODUCT FEATURES

- High performance die-cast aluminium LED floodlight with symmetrical light distribution suitable for industrial applications
- Pre-installed breathable gland prevents internal moisture accumulation
- High efficiency up to 148 Lm/W
- Non-dimmable

- High output, high efficiency floodlight
- Bracket design allows installation without removing mounting bracket
- Pre-wired with 1.5 metre of rubber insulated cable for ease of installation

| GE | NERAL INFORMATION | |
|----------------------------------|-------------------|--|
| Wattage | 50W | |
| Lumens Delivered | 7000lm | |
| Lm/W | 140lm/W | |
| Beam Angle | 115 | |
| CRI | 70 | |
| ССТ | 5000K | |
| Input | 220-240V | |
| Operating Temp | -30°C - 50°C | |
| SDCM | 5 | |
| Product Weight without Packaging | 2.032 kg | |

Belfast: +44 (0) 2890 773750

Warrington: +44 (0) 1942 433333

| TE | CHNICAL INFORMATION |
|--------------------------------|---------------------|
| Light Source | LED |
| Colour / Finish | Black |
| IP Rating | IP66 |
| IK Rating | IK08 |
| Class Protection | 1 |
| Internal / External | External |
| Surface / Recessed / Suspended | Pole, Wall |
| Lumen Depreciation | L80 54,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Height | 267 mm |









| Category | Floodlights | |
|---------------|---|--|
| Application | Ancillary, Commercial, Education, Healthcare, | |
| | Hospitality, Industrial, Outdoor, Retail | |
| Specification | Performance | |

Aztec Symmetrical

Aztec Symmetrical Floodlight 50W

Code: AAZLED50







