



Aztec



Part of the Floodlights product category

Model Aztec 2 80W Symmetric Floodlight
Code AAZT2/SYM/1
Application Commercial, Industrial, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	80W
Operating Temp	-30°C - 50°C
Lumens Delivered	14000lm (4000K)
lm/W	175lm/W
CCT	3000/4000/5000
UGR	31
Beam Angle	110

MATERIAL INFORMATION

Main Material	Aluminum, PC + tempered glass
Diffuser Material	Tempered glass
Product Weight without	3 kg
Packaging	
Colour / Finish	Black
Height	63 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	70
Internal / External	External
Surface / Recessed / Suspended	Surface
Power Factor	0.92
L70 @ 25°C	L70 100,000h

PRODUCT FEATURES

- High performance die-cast aluminium LED floodlight suitable for industrial, commercial and coastal applications
- Marine grade construction ideal for coastal and adverse weather, swimming pool and chemical plant applications
- High output, high efficiency asymmetric lens technology for anti-light pollution (asymmetric versions only)
- CCT selectable between 3000K, 4000K and 5000K
- Integral photocell with 2 x lux settings and (deleted 'on-') off options

ACCESSORIES

AAZLED/60PMA	Floodlight 60mm Pole Mount Adaptor
AAZLED/76PMA	Floodlight 76mm Pole Mount Adaptor
AAZLED/40-90PCA	Aztec Floodlight 40-90mm Pole Clamp Accessory for 50W/150W





Aztec



Part of the Floodlights product category

Model Aztec 2 80W Symmetric Floodlight
Code AAZT2/SYM/1
Application Commercial, Industrial, Retail

