





Blade

Blade Recessed Linear 600mm White OCTO
Code: ABLA060/1/W/OCTO

| | |
|---------------|---|
| Category | Commercial Linear |
| Application | Ancillary, Commercial, Education, Hospitality, Retail |
| Specification | Architectural |



PRODUCT FEATURES

- Architectural aluminium recessed linear suitable for retail, commercial and educational applications
- Perfect for recessed continuous installation to create a seamless line of light when using connector accessories and the roll-on diffuser
- Suitable for individual or continuous mounting
- Aluminium construction provides a modern and sleek appearance
- Selectable CCT between 3000K, 4000K and 6500K output
- Non-dimmable

| GENERAL INFORMATION | |
|----------------------------------|-----------------|
| Wattage | 15W |
| Lumens Delivered | 1600lm (4000k) |
| Lm/W | 105lm/W |
| Beam Angle | 110 |
| CRI | 80 |
| CCT | 3000/4000/6500K |
| Input | 220/240V |
| Operating Temp | -20°C - 45°C |
| SDCM | 6 |
| UGR | 27 |
| Energy efficiency class | C |
| Product Weight without Packaging | 0.67 kg |

| TECHNICAL INFORMATION | |
|--------------------------------|-------------|
| Light Source | LED |
| Colour / Finish | White |
| IP Rating | IP40 |
| Class Protection | 2 |
| Internal / External | Internal |
| Surface / Recessed / Suspended | Recessed |
| Lumen Depreciation | L70 54,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Height | 59 mm |

