Blade

5YR IP40 ON-SITE WARRANTY 2 YEARS

Part of the Commercial Linear product category

Model	Blade Recessed Linear 600mm White
Code	ABLA060/1/W
Application	Ancillary, Commercial, Education, Hospitality, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	15W
Operating Temp	-20°C - 45°C
Lumens Delivered	1600lm (4000k)
lm/W	105lm/W
CCT	3000/4000/6500K
UGR	27
Beam Angle	110

MATERIAL INFORMATION

Main Material	Aluminium
Diffuser Material	Polycarbonate
Product Weight without Packaging	0.67 kg
Colour / Finish	White
Height	59 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Power Factor	0.9
L70 @ 25°C	L70 B50 54,000h

PRODUCT FEATURES

- Architectural aluminium recessed linear suitable for retail, commercial and educational applications
- Aluminium construction provides a modern and sleek appearance
- Perfect for recessed continuous installation to create a seamless line of light when using connector accessories and the roll-on diffuser
- Selectable CCT between 3000K, 4000K and 6500K output
- Suitable for individual or continuous mounting





Blade

5YR IP40 ON-SITE WARRANTY 2 YEARS

Part of the Commercial Linear product category

Model	Blade Recessed Linear 600mm White
Code	ABLA060/1/W
Application	Ancillary, Commercial, Education, Hospitality, Retail

