






# Blade

Blade Recessed Linear 1200mm White OCTO  
Code: ABLA120/1/W/OCTO

Category	Commercial Linear
Application	Ancillary, Commercial, Education, Hospitality, Retail
Specification	Architectural



## PRODUCT FEATURES

- Architectural aluminium recessed linear suitable for retail, commercial and educational applications
- Perfect for recessed continuous installation to create a seamless line of light when using connector accessories and the roll-on diffuser
- Suitable for individual or continuous mounting
- Aluminium construction provides a modern and sleek appearance
- Selectable CCT between 3000K, 4000K and 6500K output
- Non-dimmable

GENERAL INFORMATION	
Wattage	30W
Lumens Delivered	3400lm (4000k)
Lm/W	113lm/W
Beam Angle	110
CRI	80
CCT	3000/4000/6500K
Input	220/240V
Operating Temp	-20°C - 45°C
SDCM	6
UGR	27
Energy efficiency class	C
Product Weight without Packaging	1.21 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP40
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 54,000h
Warranty (Years)	5
CE Mark	Yes
Height	59 mm

