Brock

5YR IP65 IK06 ON-SITE WARRANTY 2 YEARS

Part of the Bollards product category

Model	Brock Bollard Cool White
Code	ABRLEDB/650/CW
Application	Hospitality, Outdoor, Residential, Retail

GENERAL INFORMATION

Input	220-240V
Wattage	8W
Operating Temp	-20°C - 50°C
Lumens Delivered	450lm
lm/W	57lm/W
CCT	4000K
Beam Angle	50

MATERIAL INFORMATION

Diffuser Material	Polycarbonate
Product Weight without Packaging	2.235 kg
Colour / Finish	Graphite
Height	656 mm

TECHNICAL INFORMATION

Class Protection	1
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	External
Surface / Recessed / Suspended	Floor
Power Factor	0.8625
L70 @ 25°C	L70 B50 72,000h

PRODUCT FEATURES

- Modern bi-directional bollard providing vivid angled light distribution suitable for residential and hospitality applications
- Die-cast aluminium body with a graphite powder coated paint finish for enhanced durability
- Supplied c/w root mounting kit
- Available in 3000K and 4000K options
- Non-dimmable





Brock

Part of the Bollards product category

Model	Brock Bollard Cool White
Code	ABRLEDB/650/CW
Application	Hospitality, Outdoor, Residential, Retail









