



| Category | Floodlights |
|---------------|---|
| Application | Commercial, Industrial, Outdoor, Retail |
| Specification | Performance |

Calinor EVO

Calinor EVO Floodlight PIR Warm White 20W Black Code: ACAE20/1/WW/B/PIR







PRODUCT FEATURES

- Compact, slim and robust designed LED floodlight suitable for residential and commercial applications
- Toughened microprism glass for visual comfort, uniformity and durability
- Pre-wired with 1 metre of rubber insulated cable for ease of installation and easy integration
 with Floodbox accessory
- · Polycarbonate spike accessory allowing installation into lawn and garden applications

| GE | NERAL INFORMATION |
|----------------------------------|-------------------|
| Wattage | 20W |
| Lumens Delivered | 2000lm |
| Lm/W | 103lm/W |
| Beam Angle | 100 |
| CRI | 80 |
| CCT | 3000K |
| Input | 220-240V |
| Operating Temp | -15°C - 40°C |
| SDCM | 5 |
| Energy efficiency class | E |
| Product Weight without Packaging | 0.41 kg |

| TECHN | ICAL INFORMATION |
|--------------------------------|------------------|
| Light Source | LED |
| Colour / Finish | Black |
| IP Rating | IP65 |
| IK Rating | IKO6 |
| Class Protection | 1 |
| Internal / External | External |
| Surface / Recessed / Suspended | Wall |
| Lumen Depreciation | L80 69,000h |
| Warranty (Years) | 5 |
| CE Mark | Yes |
| Height | 175 mm |

Polycarbonate front trim provides excellent corrosion resistance

· Breather gland acts to minimise risk of water ingress

PIR versions complete with manual override facility

· Bracket design allows installation without removing mounting bracket

www.ansell-lighting.com

Belfast: +44 (0) 2890 773750 Warrington: +44 (0) 1942 433333



f ansellighting
ansell_lighting







| Category | Floodlights |
|---------------|---|
| Application | Commercial, Industrial, Outdoor, Retail |
| Specification | Performance |

Calinor EVO

Calinor EVO Floodlight PIR Warm White 20W Black Code: ACAE20/1/WW/B/PIR









