Comfort EVO

Part of the Downlights product category

Model	Comfort 2 CCT Downlight DALI
Code	ACOLED2/CCT/DD3
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail



GENERAL INFORMATION

Input	220-240V
Wattage	22W
Operating Temp	-20°C - 25°C
Lumens Delivered	2200lm (4000K)
lm/W	102lm/W (4000K)
CCT	3000/4000K
UGR	20
Beam Angle	80

MATERIAL INFORMATION

Product Weight without Packaging	0.66 kg
Colour / Finish	White
Diameter	230 mm
Height	100 mm

TECHNICAL INFORMATION

Class Protection	2
Light Source	LED
SDCM (Initial Macadam)	3
CRI	80
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
L70 @ 25°C	L70 B50 60,000h

PRODUCT FEATURES

- Economic high performance CCT selectable IP44 downlight suitable for commercial and healthcare applications
- Deep cut-off angle for glare control and comfort
- Osram LED technology and enhanced diffuser design for outstanding uniformity
- One product provides both 3000K and 4000K colour temperature options
- Downlight design allows installation into existing hole cut-outs from 200mm to 220mm

Comfort EVO

Part of the Downlights product category

Model	Comfort 2 CCT Downlight DALI
Code	ACOLED2/CCT/DD3
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail





