



# Comfort EVO

Part of the Downlights product category



**Model** Comfort 2 CCT Downlight DALI  
**Code** ACOLED2/CCT/DD3  
**Application** Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

## GENERAL INFORMATION

<b>Input</b>	220-240V
<b>Wattage</b>	22W
<b>Operating Temp</b>	-20°C - 25°C
<b>Lumens Delivered</b>	2200lm (4000K)
<b>lm/W</b>	102lm/W (4000K)
<b>CCT</b>	3000/4000K
<b>UGR</b>	20
<b>Beam Angle</b>	80

## MATERIAL INFORMATION

<b>Product Weight without</b>	0.66 kg
<b>Packaging</b>	
<b>Colour / Finish</b>	White
<b>Diameter</b>	230 mm
<b>Height</b>	100 mm

## TECHNICAL INFORMATION

<b>Class Protection</b>	2
<b>Light Source</b>	LED
<b>SDCM (Initial Macadam)</b>	3
<b>CRI</b>	80
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Recessed
<b>L70 @ 25°C</b>	L70 B50 60,000h

## PRODUCT FEATURES

- Economic high performance CCT selectable IP44 downlight suitable for commercial and healthcare applications
- Deep cut-off angle for glare control and comfort
- Osram LED technology and enhanced diffuser design for outstanding uniformity
- One product provides both 3000K and 4000K colour temperature options
- Downlight design allows installation into existing hole cut-outs from 200mm to 220mm





# Comfort EVO

Part of the Downlights product category



<b>Model</b>	Comfort 2 CCT Downlight DALI
<b>Code</b>	ACOLED2/CCT/DD3
<b>Application</b>	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail

