



Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail
Specification	Performance

Comfort

Comfort 2 CCT Downlight DALI

Code: ACOLED2/CCT/DD3

PRODUCT FEATURES

- Economic high performance CCT selectable IP44 downlight suitable for commercial and healthcare applications
- Osram LED technology and enhanced diffuser design for outstanding uniformity
- Downlight design allows installation into existing hole cut-outs from 200mm to 220mm
- Dimmable and Emergency options
- Deep cut-off angle for glare control and comfort
- One product provides both 3000K and 4000K colour temperature options
- Polycarbonate housing with unique thermal management for durability and optimum lifespan
- Powered by Tridonic

GENERAL INFORMATION	
Wattage	22W
Lumens Delivered	2200lm (4000K)
Lm/W	102lm/W (4000K)
Beam Angle	80
CRI	80
CCT	3000/4000K
Input	220-240V
Operating Temp	-20°C - 25°C
SDCM	3
UGR	20
Cut-Out Size	200-220mm
Product Weight without Packaging	0.66 kg

TECHNICAL INFORMATION	
Light Source	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 60,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	230 mm
Height	100 mm



Category	Downlights
Application	Ancillary, Commercial, Education, Healthcare, Hospitality, Retail
Specification	Performance

Comfort

Comfort 2 CCT Downlight DALI

Code: ACOLED2/CCT/DD3

